

Twin V-belts

PU80A orange smooth



Article no.	Dimensions	Cross section	approx. weight	Standard roll		Recommended min. pulley ØØ		Fmax/belt (s- tandard)	
	mm			cm ²	kg/100m	m	ft	mm	inch
FBSJ24X68OGB	24x6,8	1,2	14,4	30	100	60	2,4	28,8	63,4
FBSP80A21X8	21x8	1,2	14	30	100	80	3,1	28,8	63,4
FBSJ30X8OG	30x8	1,9	22,4	30	100	80	3,1	45,6	100,3
FBSJ30X8OGC	30x8	1,9	22,4	30	100	80	3,1	45,6	100,3

approx. 84° Shore A

Recommended Pretension	3...6%
------------------------	--------

Coeff. of friction μ steel approx.	0,65
--	------

Coeff. of friction μ PE approx.	0,35
-------------------------------------	------

Coeff. of friction μ HDPE approx.	0,3
---------------------------------------	-----

FDA/EC compliant

Characteristics



FDA (Food and Drug Administration)
 FDA/EC conformity for direct food contact

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 11/2024