

Twin V-belts

PU80A orange smooth, Reinforced Polyester



Article no.	Dimensions mm	Cross section cm ²	approx. weight kg/100m	Standard roll		Recommended min. pulley Ø		Fmax/belt (s- tandard)		Fmax/belt (over- lap)	
				m	ft	mm	inch	kg	lbs	kg	lbs
FBSJ21X8OGA	21x8	1,2	14,4	30	100	80	3,1	28,8	63,4	58,4	128,5
FBSJ30X8OGD	30x8	1,9	22,4	30	100	80	3,1	45,6	100,3	90,6	199,3

approx. 84° Shore A

Recommended Pretension 0,5...2%

Coeff. of friction μ steel approx. 0,65

Coeff. of friction μ PE approx. 0,35

Coeff. of friction μ HDPE approx. 0,3

FDA/EC compliant

Characteristics



FDA (Food and Drug Administration)
 FDA/EC conformity for direct food contact



with reinforcement
 for applications that require a higher pull force.

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 08/2024