


Ridge top V-belts

**PU85A blue smooth, Reinforced Glass fibre PU, weldable**



Article no.	Dimensions	Cross section	approx. weight	Standard roll		Recommended min. pulley Ø		Fmax/belt (s- tandard)		Fmax/belt (overlap)	
	mm	cm <sup>2</sup>	kg/100m	m	ft	mm	inch	kg	lbs	kg	lbs
FBZSP85A17ON	17x19	1,95	23,63	30	100	240	9,6	78	171,6	n/a	n/a
FBZSP85A22ON	22x25	3,26	39,1	30	100	280	11,2	130,4	286,9	n/a	n/a

approx. 88° Shore A

Recommended Pretension 0.5...2%

Coeff. of friction  $\mu$  steel approx. 0,6

Coeff. of friction  $\mu$  PE approx. 0,35

Coeff. of friction  $\mu$  HDPE approx. 0,3

**Characteristics**



**with reinforcement**  
 for applications that require a higher pull force.

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 08/2024