



Quality: PU85A
Article No.: FBBK22X25LGA
Color: blue



GENERAL PROFILE INFORMATION

Profile Category	Ridge top V-belts	Fmax/belt (standard)	146 kg
Profile design	with reinforcement	Fmax/Belt (overlap)	n/a
Type of reinforcement	Glass fibre PU, weldable	Weight	43,8 kg/100m
Processing Type	n/a	Temperature Range	-20°...+60°C
Recommended Min. pulley Ø	300 mm	Standard Roll	30 m
Recommended Pretension	0.5...2%	Chemical Resistance	upon request

SPECIFICATIONS

PROFILE

COATING

Type of material	Polyurethane	n/a
Approx. Material Hardness (Shore)	88° Shore A	n/a
Color	blue	n/a
Dimensions	22x25 mm	n/a
Surface	smooth	n/a
approx. Coefficient of Friction	Steel: 0,6 PE: 0,35 HDPE: 0,3	n/a
Features	with reinforcement	n/a
n/a	n/a	n/a
n/a	n/a	n/a
n/a	n/a	n/a
n/a	n/a	n/a
n/a	n/a	n/a

CONFORMITY

The statements above are results of the in-house quality testing. They contain no guarantee of properties and in particular do not contain statements about the suitability of the product for a specific purpose, so that no claims against us can be derived. The information does not relieve the purchaser in particular by its commitment to the input control.

Subject to change without notice - 08/2024