



**Quality:** PU75A  
**Article No.:** FBRP75A150  
**Color:** red

#### GENERAL PROFILE INFORMATION

Profile Category	Round belts	Fmax/belt (standard)	45,1 kg
Profile design	Without reinforcement	Fmax/Belt (overlap)	n/a
Type of reinforcement	n/a	Weight	21,5 kg/100m
Processing Type	n/a	Temperature Range	-20°...+60°C
Recommended Min. pulley Ø	120 mm	Standard Roll	50 m
Recommended Pretension	4...8%	Chemical Resistance	upon request

#### SPECIFICATIONS

#### PROFILE

#### COATING

Type of material	Polyurethane	n/a
Approx. Material Hardness (Shore)	80° Shore A	n/a
Color	red	n/a
Diameter Ø	15 mm (19/32 inch)	n/a
Surface	smooth	n/a
approx. Coefficient of Friction	Steel: 0.7   PE: 0.4   HDPE: 0.35	n/a
Features	n/a	n/a
n/a	n/a	n/a
n/a	n/a	n/a
n/a	n/a	n/a
n/a	n/a	n/a
n/a	n/a	n/a

#### CONFORMITY

The statements above are results of the in-house quality testing. They contain no guarantee of properties and in particular do not contain statements about the suitability of the product for a specific purpose, so that no claims against us can be derived. The information does not relieve the purchaser in particular by its commitment to the input control.

Subject to change without notice - 11/2024