



Quality: PU85A Article No.: FBRP85A030R Color: green

GENERAL PROFILE INFORMATION			
Profile Category	Round belts	Fmax/belt (standard)	2,7 kg
Profile design	Without reinforcement	Fmax/Belt (overlap)	n/a
Type of reinforcement	n/a	Weight	0,9 kg/100m
Processing Type	n/a	Temperature Range	-20°+60°C
Recommended Min. pulley Ø	25 mm	Standard Roll	200 m
Recommended Pretension	48%	Chemical Resistance	upon request
SPECIFICATIONS	PROFILE	COATING	
Type of material	Polyurethane	n/a	

Polyurethane	n/a
88° Shore A	n/a
green	n/a
3 mm (1/8 inch)	n/a
roughened	n/a
Steel: 0,45 PE: 0,3 HDPE: 0,25	n/a
n/a	n/a
	88° Shore A green 3 mm (1/8 inch) roughened Steel: 0,45 PE: 0,3 HDPE: 0,25 n/a n/a n/a n/a n/a n/a n/a n/a

CONFORMITY

The statements above are results of the in-house quality testing. They contain no guarantee of properties and in particular do not contain statements about the suitability of the product for a specific purpose, so that no claims against us can be derived. The information does not relieve the purchaser in particular by its commitment to the input control.

Subject to change without notice - 04/2025