



6.3

Quality: PU85A Article No.: FBRP85A063R Color: green

GENERAL PROFILE INFORMATION			
Profile Category	Round belts	Fmax/belt (standard)	11,4 kg
Profile design	Without reinforcement	Fmax/Belt (overlap)	n/a
Type of reinforcement	n/a	Weight	3,8 kg/100m
Processing Type	n/a	Temperature Range	-20°+60°C
Recommended Min. pulley Ø	65 mm	Standard Roll	100 m
Recommended Pretension	48%	Chemical Resistance	upon request

PROFILE	COATING
Polyurethane	n/a
88° Shore A	n/a
green	n/a
6,3 mm (1/4 inch)	n/a
roughened	n/a
Steel: 0,45   PE: 0,3   HDPE: 0,25	n/a
n/a	n/a
	Polyurethane88° Shore Agreen6,3 mm (1/4 inch)roughenedSteel: 0,45   PE: 0,3   HDPE: 0,25n/an/an/an/an/an/an/an/an/an/a

## CONFORMITY

The statements above are results of the in-house quality testing. They contain no guarantee of properties and in particular do not contain statements about the suitability of the product for a specific purpose, so that no claims against us can be derived. The information does not relieve the purchaser in particular by its commitment to the input control.

Subject to change without notice - 04/2025