



10

Quality: PU85A Article No.: FBRP85A100R Color: green

GENERAL PROFILE INFORMATION					
Profile Category	Round belts	Fmax/belt (standard)	28,6 kg		
Profile design	Without reinforcement	Fmax/Belt (overlap)	n/a		
Type of reinforcement	n/a	Weight	9,4 kg/100m		
Processing Type	n/a	Temperature Range	-20°+60°C		
Recommended Min. pulley Ø	100 mm	Standard Roll	50 m		
Recommended Pretension	48%	Chemical Resistance	upon request		
SPECIFICATIONS	PROFILE	COATING			
Type of material	Polyurethane	n/a			
Approx. Material Hardness (Shore)	88° Shore A	n/a			
Color	green	n/a			

10 mm (7/16 inch)

Steel: 0,45 | PE: 0,3 | HDPE: 0,25

roughened

n/a

CON	FOR	7
CON		

Diameter Ø

approx. Coefficient of Friction

Surface

Features

n/a

n/a

n/a

n/a

n/a

The statements above are results of the in-house quality testing. They contain no guarantee of properties and in particular do not contain statements about the suitability of the product for a specific purpose, so that no claims against us can be derived. The information does not relieve the purchaser in particular by its commitment to the input control.

Subject to change without notice - 04/2025