



Quality: TPE40D
Article No.: FBRKO40D080
Color: beige



GENERAL PROFILE INFORMATION

Profile Category	Round belts	Fmax/belt (standard)	30,1 kg
Profile design	Without reinforcement	Fmax/Belt (overlap)	n/a
Type of reinforcement	n/a	Weight	6 kg/100m
Processing Type	n/a	Temperature Range	-30°...+60°C
Recommended Min. pulley Ø	90 mm	Standard Roll	100 m
Recommended Pretension	2...4%	Chemical Resistance	upon request

SPECIFICATIONS

PROFILE

COATING

Type of material	Polyester	n/a
Approx. Material Hardness (Shore)	40D / 95A	n/a
Color	beige	n/a
Diameter Ø	8 mm (5/16 inch)	n/a
Surface	smooth	n/a
approx. Coefficient of Friction	Steel: 0,5 PE: 0,25 HDPE: 0,2	n/a
Features	FDA (Food and Drug Administration)	n/a
n/a	Cold-flexible	n/a
n/a	n/a	n/a
n/a	n/a	n/a
n/a	n/a	n/a
n/a	n/a	n/a

CONFORMITY

REACH EC 1907/2006 in the current versions

EC 1935/2004 in the current versions

EC 10/2011 in the current versions

FDA (Food and Drug Administration)

The statements above are results of the in-house quality testing. They contain no guarantee of properties and in particular do not contain statements about the suitability of the product for a specific purpose, so that no claims against us can be derived. The information does not relieve the purchaser in particular by its commitment to the input control.

Subject to change without notice - 04/2025