


Sidewalls

PU80A ultramarine blue smooth



approx. 84° Shore A

FDA/EC compliant

N° d'article	Height H		Wave width B	Base width B1	Pitch off waves A	approx. weight g/m	Standard roll m	Pulley diameter ?ø		
	mm	inch						Minimum mm	Recommended mm	Counterflex mm
FBV FH020LB	20	0,79	23	32	25,4	174	100	35	70	70
FBV FH030LB	30	1,18	23	32	25,4	220	100	55	80	110
FBV FH040LB	40	1,57	23	32	25,4	265	100	75	90	150
FBV FH050LB	50	1,97	23	32	25,4	310	100	80	100	160
FBV FH060LB	60	2,36	45	55	50,8	445	100	90	110	180
FBV FH080LB	80	3,15	45	55	50,8	544	50	125	130	250
FBV FH100LB	100	3,94	45	55	50,8	642	50	155	160	310
FBV FH120LB	120	4,72	45	55	50,8	741	50	170	185	340

The statements above are results of the in-house quality testing. They contain no guarantee of properties and in particular do not contain statements about the suitability of the product for a specific purpose, so that no claims against us can be derived. The information does not relieve the purchaser in particular by its commitment to the input control.

Subject to change without notice - 11/2024