


V-Belts

PU75A sky blue smooth



Article no.	Dimensions	Cross section	approx. weight	Standard roll		Recommended min. pulley Ø		Fmax/belt (standard)	
	mm	cm ²	kg/100m	m	ft	mm	inch	kg	lbs
FBKI6YLGA	6x4 (Y)	0,19	2,3	100	328	35	1,4	4,6	10,1
FBKI8MLGA	8x5 (M)	0,32	4	100	328	40	1,6	7,6	15,8
FBKI10ZLGA	10x6 (Z)	0,48	6	50	164	50	2	11,6	25,5
FBKI13ALGA	13x8 (A)	0,82	10	50	164	75	3	19,6	43,1
FBKI17BLGA	17x11 (B)	1,46	18	50	164	100	3,9	35	77

approx. 80° Shore A

Recommended Pretension 4...8%

Coeff. of friction μ steel approx. 0,7

Coeff. of friction μ PE approx. 0,4

Coeff. of friction μ HDPE approx. 0,35

FDA/EC compliant

Characteristics



Hydrolysis resistance
Hydrolysis resistance (HY). Suitable for humid environments.



microbial resistant
Microbial resistant materials do not provide a breeding ground for microorganisms.



Cold-flexible
Particularly flexible at low temperatures down to -30°C



FDA (Food and Drug Administration)
FDA/EC conformity for direct food contact

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 11/2024