

V-Belts

**PU75A orange smooth, Reinforced Glass fibre PU, weldable**



Article no.	Dimensions	Cross section	approx. weight	Standard roll		Recommended min. pulley Ø		Fmax/belt (s- tandard)		Fmax/belt (overlap)	
	mm	cm <sup>2</sup>	kg/100m	m	ft	mm	inch	kg	lbs	kg	lbs
FBZKP75A13GL	13x8 (A)	0,82	10	50	164	110	4,4	25,3	55,6		
FBZKP75A17GL	17x11 (B)	1,46	18	50	164	140	5,5	45	98,9		
FBZKP75A22GL	22x14 (C)	2,4	29	50	164	180	7,1	66,2	145,7		

approx. 80° Shore A

Recommended Pretension 0,5...2%

Coeff. of friction  $\mu$  steel approx. 0,7

Coeff. of friction  $\mu$  PE approx. 0,4

Coeff. of friction  $\mu$  HDPE approx. 0,35

**Characteristics**



**with reinforcement**  
 for applications that require a higher pull force.

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 08/2024