

V-Belts

PU75A red smooth



approx. 80° Shore A	
Recommended Pretension	4...8%
Coeff. of friction μ steel approx.	0,7
Coeff. of friction μ PE approx.	0,4
Coeff. of friction μ HDPE approx.	0,35

Article no.	Dimensions	Cross section cm ²	approx. weight kg/100m	Standard roll		Recommended min. pulley ØØ		Fmax/belt (s- tandard)	
	mm			m	ft	mm	inch	kg	lbs
FBKP75A06	6x4 (Y)	0,19	2,3	100	328	35	1,4	4,9	10,8
FBKP75A08	8x5 (M)	0,32	4	100	328	40	1,6	8,2	18,1
FBKP75A10	10x6 (Z)	0,48	6	50	164	50	2	12,2	26,7
FBKP75A13	13x8 (A)	0,82	10	50	164	75	3	20,6	45,3
FBKP75A17	17x11 (B)	1,46	18	50	164	100	3,9	37,2	81,9
FBKP75A22	22x14 (C)	2,4	29	50	164	145	5,7	60,8	133,7
FBKP75A32	32x20 (D)	5	62	25	82	210	8,3	127,4	280,3

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 04/2025