


V-Belts

PU80A capri blue smooth



approx. 84° Shore A

Recommended Pretension 3...6%

Coeff. of friction μ steel approx. 0,65

Coeff. of friction μ PE approx. 0,35

Coeff. of friction μ HDPE approx. 0,3

FDA/EC compliant

Article no.	Dimensions	Cross section cm ²	approx. weight kg/100m	Standard roll		Recommended min. pulley ØØ		Fmax/belt (standard)	
	mm			m	ft	mm	inch	kg	lbs
FBKJ6YLGM	6x4 (Y)	0,19	2,3	100	328	40	1,6	4,6	10,2
FBKJ8MLGM	8x5 (M)	0,32	4	100	328	45	1,8	7,7	16,9
FBKJ10ZLGM	10x6 (Z)	0,48	6	50	164	55	2,2	11,5	25,3
FBKJ13ALGM	13x8 (A)	0,82	10	50	164	85	3,3	19,7	43,3
FBKJ17BLGM	17x11 (B)	1,46	18	50	164	110	4,3	35	77,1
FBKJ22CLGM	22x14 (C)	2,4	29	50	164	150	6	57,6	126,7

Characteristics



Metal detectable



X-ray detectable



FDA (Food and Drug Administration)

FDA/EC conformity for direct food contact

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 04/2025