


V-Belts

PU85A green smooth



approx. 88° Shore A

Recommended Pretension 4...8%

Coeff. of friction μ steel approx. 0,6

Coeff. of friction μ PE approx. 0,35

Coeff. of friction μ HDPE approx. 0,3

Article no.	Dimensions	Cross section cm ²	approx. weight kg/100m	Standard roll		Recommended min. pulley Ø		Fmax/belt (s- tandard)	
	mm			m	ft	mm	inch	kg	lbs
FBKP85A06	6x4 (Y)	0,19	2,3	100	328	45	1,8	6,9	15,3
FBKP85A08	8x5 (M)	0,32	4	100	328	50	2	11,6	25,6
FBKP85A10	10x6 (Z)	0,48	6	50	164	65	2,6	17,5	38,6
FBKP85A13	13x8 (A)	0,82	10	50	164	95	3,8	30	66
FBKP85A17	17x11 (B)	1,46	18	50	164	120	4,7	53	116,7
FBKP85A22	22x14 (C)	2,4	29	50	164	165	6,5	87,7	193
FBKP85A32	32x20 (D)	5	62	25	82	250	9,8	195,8	430,8

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 04/2025