





Quality: PU90A

Article No.: FBZKP90A17P

Color: white



GENERAL PROFILE INFORMATION				
Profile Category	V-belts	Fmax/belt (standard)	69,1 kg	
Profile design	with reinforcement	Fmax/Belt (overlap)	120 kg	
Type of reinforcement	Polyester	Weight	18 kg/100m	
Processing Type	n/a	Temperature Range	-20°+60°C	
Recommended Min. pulley Ø	150 mm	Standard Roll	50 m	
Recommended Pretension	0.52%	Chemical Resistance	upon request	

SPECIFICATIONS	PROFILE	COATING
Type of material	Polyurethane	n/a
Approx. Material Hardness (Shore)	92° Shore A	n/a
Color	white	n/a
Dimensions	17x11 mm (B)	n/a
Surface	smooth	n/a
approx. Coefficient of Friction	Steel: 0,5 PE: 0,3 HDPE: 0,25	n/a
Features	with reinforcement	n/a
n/a	n/a	n/a

CONFORMITY

The statements above are results of the in-house quality testing. They contain no guarantee of properties and in particular do not contain statements about the suitability of the product for a specific purpose, so that no claims against us can be derived. The information does not relieve the purchaser in particular by its commitment to the input control.

Subject to change without notice - 04/2025