

V-Belts

PU95A beige smooth, Reinforced Polyester



Article no.	Dimensions	Cross section	approx. weight	Standard roll		Recommended min. pulley Ø		Fmax/belt (standard)		Fmax/belt (overlap)	
	mm	cm ²	kg/100m	m	ft	mm	inch	kg	lbs	kg	lbs
FBKM13ABGA	13x8 (A)	0,82	10	50	164	130	5	40	88	67,5	148,5
FBKM17BBGA	17x11 (B)	1,46	18	50	164	175	6,8	72	158,4	120	264
FBKM22CBGA	22x14 (C)	2,4	29	50	164	250	9,7	120	264	202	444,4

approx. 95° Shore A

Recommended Pretension 0.5...2%

Coeff. of friction μ steel approx. 0,45

Coeff. of friction μ PE approx. 0,25

Coeff. of friction μ HDPE approx. 0,2

FDA/EC compliant

Characteristics



FDA (Food and Drug Administration)
 FDA/EC conformity for direct food contact



with reinforcement
 for applications that require a higher pull force.

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 08/2024