

V-Belts

TPE55D beige smooth, Reinforced Polyester



Article no.	Dimensions	Cross section cm ²	approx. weight kg/100m	Standard roll		Recommended min. pulley Ø		Fmax/belt (standard)		Fmax/belt (overlap)	
	mm			m	ft	mm	inch	kg	lbs	kg	lbs
FBKH55D10P	10x6 (Z)	0,48	6	50	164	110	4,4	48	105,6	70	154
FBKH55D13P	13x8 (A)	0,82	10	50	164	135	5,3	80	176	110	242
FBKH55D17P	17x11 (B)	1,46	18	50	164	190	7,2	146	321,2	180	396
FBKH55D22P	22x14 (C)	2,4	29	50	164	260	10,2	240	528	300	660

approx. 55D / 100A

Recommended Pretension 0.5...2%

Coeff. of friction μ steel approx. 0,35

Coeff. of friction μ PE approx. 0,2

Coeff. of friction μ HDPE approx. 0,15

FDA/EC compliant

Characteristics



FDA (Food and Drug Administration)
 FDA/EC conformity for direct food contact



with reinforcement
 for applications that require a higher pull force.

The above information is the result of in-house quality testing. They do not contain any guarantee of properties and in particular do not contain any statements about the suitability of the product for specific purposes, so that no claims against us can be derived from them. In particular, the information does not release the purchaser from his obligation to inspect incoming goods.

Subject to change without notice - 11/2024