


V-guides

**PU60A transparent smooth**



ca. 65° Shore A

Coeff. of friction  $\mu$  steel approx. 0,85

Coeff. of friction  $\mu$  PE approx. 0,5

Coeff. of friction  $\mu$  HDPE approx. 0,45

| Order No.  | Profile dimension<br>mm | Standard roll |     | Recommended min. pulley $\varnothing$ |      |
|------------|-------------------------|---------------|-----|---------------------------------------|------|
|            |                         | m             | ft  | mm                                    | inch |
| FBKF6YTGD  | 6x4 (Y)                 | 150           | 492 | 20                                    | 0,8  |
| FBKF8MTGD  | 8x5 (M)                 | 150           | 492 | 25                                    | 1    |
| FBKF10ZTGD | 10x6 (Z)                | 150           | 492 | 30                                    | 1,2  |
| FBKF13ATGD | 13x8 (A)                | 150           | 492 | 45                                    | 1,8  |
| FBKF17BTGD | 17x11 (B)               | 100           | 328 | 60                                    | 2,4  |
| FBKF22CTGD | 22x14 (C)               | 50            | 164 | 85                                    | 3,3  |

The statements above are results of the in-house quality testing. They contain no guarantee of properties and in particular do not contain statements about the suitability of the product for a specific purpose, so that no claims against us can be derived. The information does not relieve the purchaser in particular by its commitment to the input control.

Subject to change without notice - 04/2025