

V-guides
PU65A transparent smooth



ca. 72° Shore A

Coeff. of friction μ steel approx. 0,8

Coeff. of friction μ PE approx. 0,45

Coeff. of friction μ HDPE approx. 0,4

Order No.	Profile dimension mm	Standard roll		Recommended min. pulley \varnothing	
		m	ft	mm	inch
FBKG5X3TG	5x3	150	492	20	0,8
FBKG6YTG	6x4 (Y)	150	492	30	1,2
FBKG8MTG	8x5 (M)	150	492	35	1,4
FBKG10ZTG	10x6 (Z)	150	492	40	1,6
FBKG13ATG	13x8 (A)	150	492	65	2,6
FBKG17BTG	17x11 (B)	100	328	85	3,4
FBKG22CTG	22x14 (C)	50	164	120	4

Characteristics



Hydrolysis resistance
Hydrolysis resistance (HY).
Suitable for humid environments.



microbial resistant
Microbial resistant materials do not provide a breeding ground for microorganisms.



FDA (Food and Drug Administration)
FDA/EC conformity for direct food contact

The statements above are results of the in-house quality testing. They contain no guarantee of properties and in particular do not contain statements about the suitability of the product for a specific purpose, so that no claims against us can be derived. The information does not relieve the purchaser in particular by its commitment to the input control.

Subject to change without notice - 04/2025