


V-guides

PU65A transparent smooth



ca. 72° Shore A

Coeff. of friction μ steel 0,8
 approx.

Coeff. of friction μ PE 0,45
 approx.

Coeff. of friction μ HDPE 0,4
 approx.

| Order No. | Profile dimension mm | Standard roll | | Recommended min. pulley \varnothing | |
|------------|-------------------------|---------------|-----|---------------------------------------|------|
| | | m | ft | mm | inch |
| FBKG6YTGA | 6x4 (Y) | 150 | 492 | 25 | 1 |
| FBKG8MTGA | 8x5 (M) | 150 | 492 | 28 | 1,1 |
| FBKG10ZTGA | 10x6 (Z) | 150 | 492 | 30 | 1,2 |
| FBKG13ATGA | 13x8 (A) | 150 | 492 | 40 | 1,6 |
| FBKG17BTGA | 17x11 (B) | 100 | 328 | 55 | 2,2 |
| FBKG22CTGA | 22x14 (C) | 50 | 164 | 90 | 3,5 |

Characteristics



Hydrolysis resistance
 Hydrolysis resistance (HY).
 Suitable for humid environments.



microbial resistant
 Microbial resistant materials do not provide a breeding ground for microorganisms.



FDA (Food and Drug Administration)
 FDA/EC conformity for direct food contact

The statements above are results of the in-house quality testing. They contain no guarantee of properties and in particular do not contain statements about the suitability of the product for a specific purpose, so that no claims against us can be derived. The information does not relieve the purchaser in particular by its commitment to the input control.

Subject to change without notice - 11/2024