


V-guides
PU65A transparent smooth



ca. 72° Shore A

Coeff. of friction μ steel approx. 0,8

Coeff. of friction μ PE approx. 0,45

Coeff. of friction μ HDPE approx. 0,4

Order No.	Profile dimension mm	Standard roll		Recommended min. pulley \varnothing	
		m	ft	mm	inch
FBKG6YTGA	6x4 (Y)	150	492	25	1
FBKG8MTGA	8x5 (M)	150	492	28	1,1
FBKG10ZTGA	10x6 (Z)	150	492	30	1,2
FBKG13ATGA	13x8 (A)	150	492	40	1,6
FBKG17BTGA	17x11 (B)	100	328	55	2,2
FBKG22CTGA	22x14 (C)	50	164	90	3,5

Characteristics



Hydrolysis resistance
Hydrolysis resistance (HY).
Suitable for humid environments.



microbial resistant
Microbial resistant materials do not provide a breeding ground for microorganisms.



FDA (Food and Drug Administration)
FDA/EC conformity for direct food contact

The statements above are results of the in-house quality testing. They contain no guarantee of properties and in particular do not contain statements about the suitability of the product for a specific purpose, so that no claims against us can be derived. The information does not relieve the purchaser in particular by its commitment to the input control.

Subject to change without notice - 04/2025