


V-guides

**PU70A capri blue smooth**



ca. 76° Shore A

Coeff. of friction  $\mu$  steel 0,75  
 approx.

Coeff. of friction  $\mu$  PE 0,4  
 approx.

Coeff. of friction  $\mu$  HDPE 0,35  
 approx.

Order No.	Profile dimension mm	Standard roll		Recommended min. pulley $\varnothing$	
		m	ft	mm	inch
FBKF6YLGB	6x4 (Y)	150	492	25	1
FBKF8MLGB	8x5 (M)	150	492	30	1,2
FBKF10ZLGB	10x6 (Z)	150	492	35	1,4
FBKF13ALGB	13x8 (A)	150	492	55	2,1
FBKF17BLGB	17x11 (B)	100	328	70	2,8
FBKF22CLGB	22x14 (C)	50	164	100	3,9

**Characteristics**



**Metal detectable**



**X-ray detectable**



**FDA (Food and Drug Administration)**

FDA/EC conformity for direct food contact

The statements above are results of the in-house quality testing. They contain no guarantee of properties and in particular do not contain statements about the suitability of the product for a specific purpose, so that no claims against us can be derived. The information does not relieve the purchaser in particular by its commitment to the input control.

Subject to change without notice - 08/2024