


BEHAbelt PUsoft

Flexible and tactile



BEST PROPERTIES

BEHAbelt PUsoft - the highly flexible, grippy and durable solution for applications with very small pulley diameters.

The unique BEHAbelt mixture of PU combines excellent grip properties due to the high friction coefficient with simultaneous low.

BEHAbelt PUsoft - THE alternative to silicone.



Extremely flexible; suitable for smallest diameters.



Extremely high grip.



Excellent Weldability.



Excellent resistance to oil, grease or chemicals.



100% made of polyurethane.



FDA/EC compliant.

APPLICATION EXAMPLES

- Slicers for the food industry
- Dough winding machine
- Sealing industry
- Labeling and packaging industry



We would be glad to advise you!
+49 (0) 7684/907-0

TECHNICAL DATA

BEHAbelt PUsoft PU 65A blue matt

Shore A:	ca. 65°	
Coefficient of friction		
μ approx.:	Steel 0,75 / PE 0,45 / HDPE 0,35	
Recommended pretension:	10 - 12 %	
Profile	Fmax/Belt	Min.-Pulley-Ø
mm	daN	mm
3,0	0,9	10
4,0	1,7	20
5,0	2,7	30
6,0	3,9	40

Good oil and grease resistance, hydrolysis